




**Hochfeste Kette EN 818-2**  
schwarz lackiert

**Alloy Grade 80 chain acc. to EN 818-2**  
black varnished

| Nennstärke<br>nominal chain<br>thickness | Tragfähigkeit<br>WLL<br>kg | t<br>mm | b<br>≈ mm | Gewicht per<br>m in kg<br>weight<br>per m in kg | Fasslänge<br>length in<br>drums<br>m | Artikelnummer<br>stock no. | Bundlänge<br>length in<br>bundles<br>m | Artikelnummer<br>stock no. |
|--|----------------------------|---------|-----------|---|--------------------------------------|----------------------------|--|----------------------------|
| 6-8                                      | 1120                       | 18      | 8         | 0,8   | 200                                  | 299 713 006                | 50                                     | 299 711 006                |
| 7-8                                      | 1500                       | 21      | 10,5      | 1,1   | 200                                  | 299 713 007                | 50                                     | 299 711 007                |
| 8-8                                      | 2000                       | 24      | 10,8      | 1,5   | 200                                  | 299 713 008                | 50                                     | 299 711 008                |
| 10-8                                     | 3150                       | 30      | 13,5      | 2,3   | 200                                  | 299 713 010                | 50                                     | 299 711 010                |
| 13-8                                     | 5300                       | 39      | 17,5      | 3,8   | 150                                  | 299 713 013                | 25                                     | 299 711 013                |
| 16-8                                     | 8000                       | 48      | 21,5      | 6,1   | 75                                   | 299 713 016                | 25                                     | 299 711 016                |
| 18-8                                     | 10000                      | 54      | 24,3      | 7,3   | -                                    | -                          | 25                                     | 299 711 018                |
| 19-8                                     | 11200                      | 57      | 25        | 8,5   | -                                    | -                          | 25                                     | 299 711 019                |
| 20-8                                     | 12500                      | 60      | 27        | 9,0   | -                                    | -                          | 25                                     | 299 711 020                |
| 22-8                                     | 15000                      | 66      | 29,5      | 10,9  | -                                    | -                          | 25                                     | 299 711 022                |
| 26-8                                     | 21200                      | 78      | 35        | 15,2  | -                                    | -                          | 25                                     | 299 711 026                |
| 32-8                                     | 31500                      | 96      | 41,6      | 23,0  | -                                    | -                          | 25                                     | 299 711 032                |



**Hochfeste Kette EN 818-2**  
mit Langzeit-Korrosionsschutz **SP100**

**Alloy Grade 80 chain acc. to EN 818-2**  
with **SP100** corrosion protection

| Nennstärke<br>nominal chain<br>thickness | Tragfähigkeit<br>WLL<br>kg | t<br>mm | b<br>≈ mm | Gewicht per<br>m in kg<br>weight<br>per m in kg | Fasslänge<br>length in<br>drums<br>m | Artikelnummer<br>stock no. | Bundlänge<br>length in<br>bundles<br>m | Artikelnummer<br>stock no. |
|--|----------------------------|---------|-----------|---|--------------------------------------|----------------------------|--|----------------------------|
| 6-8                                      | 1120                       | 18      | 8         | 0,8   | 300                                  | 299 621 006                | 50                                     | 299 620 006                |
| 7-8                                      | 1500                       | 21      | 10,5      | 1,1   | 250                                  | 299 621 007                | 50                                     | 299 620 007                |
| 8-8                                      | 2000                       | 24      | 10,8      | 1,5   | 200                                  | 299 621 008                | 50                                     | 299 620 008                |
| 10-8                                     | 3150                       | 30      | 13,5      | 2,3   | 200                                  | 299 621 010                | 50                                     | 299 620 010                |
| 13-8                                     | 5300                       | 39      | 17,5      | 3,8   | 125                                  | 299 621 013                | 25                                     | 299 620 013                |
| 16-8                                     | 8000                       | 48      | 21,5      | 6,1   | 50                                   | 299 621 016                | 25                                     | 299 620 016                |

