



Turnbuckles with trapezoid thread

Stock No.	WLL (t)	L min (mm)	L max (mm)	Take-up (mm)	Thread (trap.)	Dimensions (mm)				Weight (kg)
						A	ØJ	K	L	
41.001.60.22	1.6	450	638	188	22 x 5	240	16	26	58	2
41.002.00.22	2	470	670	200	24 x 5	260	16	26	58	3
41.002.50.22	2.5	538	754	216	28 x 5	280	20	32	72	5
41.003.10.22	3.1	558	786	228	30 x 6	300	20	32	72	7
41.004.00.22	4	635	876	241	32 x 6	320	25	40	94	9
41.005.00.22	5	658	898	240	36 x 6	340	25	40	94	13
41.006.30.22	6.3	753	1016	263	44 x 7	380	30	45	108	19
41.008.00.22	8	813	1110	297	48 x 8	420	32	50	115	27
41.010.00.22	10	891	1200	309	52 x 8	460	36	60	125	35
41.012.60.22	12.6	988	1328	340	55 x 9	500	40	65	144	46
41.016.00.22	16	1092	1446	354	65 x 10	540	45	70	163	64
41.020.00.22	20	1184	1566	382	70 x 10	580	55	75	173	78
41.025.00.22	25	1270	1674	404	75 x 10	620	60	80	192	90
41.031.50.22	31.5	1382	1812	430	80 x 10	660	60	90	216	130

Minimum Ultimate Strength = 5 x WLL.

- Standard painted blue, but can be supplied in any color or galvanized.
- Available in all combinations of eyes, stud eyes and welding ends. • Factory supplied with lock nuts.
- Lock plates or special locking devices possible. • Can be supplied with turning wheel or ratchet. • Other sizes possible.
- Straight or in-line pull only.