



Turnbuckles with trapezoid thread

Stock No.	WLL (t)	L min (mm)	L max (mm)	Take-up (mm)	Thread (trap.)	Dimensions (mm)				Weight (kg)
						A	ØQ	S	T	
41.001.60.33	1.6	349	537	188	22 x 5	240	23	22.5	20	2
41.002.00.33	2	377	577	200	24 x 5	260	25	25	22	3
41.002.50.33	2.5	411	617	206	28 x 5	280	27	27.5	25	5
41.003.10.33	3.1	438	666	228	30 x 6	300	30	30	28	6
41.004.00.33	4	472	713	241	32 x 6	320	33	32.5	30	8
41.005.00.33	5	511	751	240	36 x 6	340	39	37.5	35	11
41.006.30.33	6.3	577	840	263	44 x 7	380	42	42.5	40	15
41.008.00.33	8	635	932	297	48 x 8	420	48	47.5	45	23
41.010.00.33	10	703	1012	309	52 x 8	460	52	55	50	30
41.012.60.33	12.6	762	1102	340	55 x 9	500	56	60	55	40
41.016.00.33	16	839	1193	354	65 x 10	540	65	65	60	55
41.020.00.33	20	904	1286	382	70 x 10	580	74	70	65	69
41.025.00.33	25	968	1372	404	75 x 10	620	78	75	70	78
41.031.50.33	31.5	1040	1470	430	80 x 10	660	86	85	80	113
41.040.00.33	40	1186	1681	495	90 x 10	695	96	95	90	136
41.050.00.33	50	1286	1836	550	100 x 10	770	106	105	100	160
41.063.00.33	63	1406	2011	605	110 x 10	845	116	115	110	220
41.080.00.33	80	1541	2201	660	120 x 10	920	131	135	125	280
41.100.00.33	100	1662	2377	715	130 x 10	995	146	148	140	370
41.125.00.33	125	1804	2574	770	140 x 10	1070	168	168	160	500
41.160.00.33	160	2028	2908	880	160 x 10	1220	188	190	180	725

Minimum Ultimate Strength = 5 x WLL.

- Standard painted blue, but can be supplied in any color or galvanized.
- Available in all combinations of eyes, stud eyes and welding ends. • Factory supplied with lock nuts.
- Lock plates or special locking devices possible. • Can be supplied with turning wheel or ratchet. • Other sizes possible.
- Straight or in-line pull only.