



Turnbuckles with metric thread

Stock No.	WLL (t)	MBL (t)	Thread	L min (mm)	L max (mm)	Take up (mm)	Dimensions (mm)					Weight (kg)
							A	P	U	V	W	
42.000.30.11A	0.3	1.5	M8	203	305	102	127	6	21	9	9	0.2
42.000.50.11A	0.5	2.5	M10	245	355	110	160	8	21	9	11	0.3
42.000.70.11A	0.7	3.5	M12	345	525	180	230	10	35	13	19	0.8
42.001.20.11A	1.2	6	M16	395	565	170	230	12	50	16	21	1.4
42.001.50.11A	1.5	7.5	M20	395	555	160	230	16	46	18	21	2.2
42.002.20.11A	2.2	11	M22	476	702	226	305	20	60	20	25	3.5
42.003.20.11A	3.2	16	M24	580	860	280	360	22	63	24	30	4.1
42.003.80.11A	3.8	19	M27	600	870	270	356	22	63	24	31	4.5
42.005.00.11A	5	25	M33	650	930	280	385	24	74	30	38	6.4
42.006.30.11A	6.3	31.5	M36	680	910	230	385	30	85	30	48	11
42.007.00.11A	7	35	M39	670	949	279	407	34	90	32	47	11
42.008.50.11A	8.5	42.5	M45	780	1020	240	410	35	120	43	50	19
42.010.00.11A	10	55	M48	743	977	234	407	43	121	46	51	22
42.012.60.11	12.6	63	M56	862	1202	340	500	52	122	60	65	39
42.016.00.11	16	80	M64	925	1280	355	540	60	130	65	70	48

Minimum Ultimate Strength = 5 x WLL.

- Standard hot dip galvanized.
- Factory supplied with locking nuts.
- Testing on request (at additional costs).
- Bolt secured with nut and split pin.
- Straight or in-line pull only.