



Turnbuckles with metric thread

Stock No.	WLL (t)	MBL (t)	Thread	L min (mm)	L max (mm)	Take up (mm)	Dimensions (mm)				Weight (kg)
							A	J	K	L	
42.000.30.22A	0.3	1.5	M8	203	305	102	127	8	9	20	0.3
42.000.50.22A	0.5	2.5	M10	235	349	114	152	8	11	25	0.4
42.000.70.22A	0.7	3.5	M12	330	530	200	229	11	14	36	0.9
42.001.20.22A	1.2	6	M16	377	560	183	229	14	18	40	1.2
42.001.50.22A	1.5	7.5	M20	410	565	155	229	17	25	55	2.0
42.002.20.22A	2.2	11	M22	486	730	244	305	17	25	55	3.1
42.003.20.22A	3.2	16	M24	556	856	300	356	20	26	57	3.9
42.003.80.22A	3.8	19	M27	576	856	280	356	20	26	57	4.8
42.005.00.22A	5	25	M33	640	920	280	381	25	34	64	6.8
42.006.30.22A	6.3	31.5	M36	650	920	270	381	27	38	75	9
42.007.00.22A	7	35	M39	687	970	283	407	27	38	75	10.0
42.008.50.22A	8.5	42.5	M45	720	1020	300	407	30	40	85	14.0
42.010.00.22A	10	50	M48	770	1050	280	407	37	44	92	18.0

Minimum Ultimate Strength = 5 x WLL.

- Standard hot dip galvanized.
- Factory supplied with locking nuts.
- Testing on request (at additional costs).
- Bolt secured with nut and split pin.
- Straight or in-line pull only.