



Stock No.	WLL (t)	Wire d (mm)	Dimensions (mm)											Weight (kg)
			ØD1	ØD2	B	O	R	S	TA	TB	TL	T	ØZ	
21.250.05.11-11	5	11	250	210	348	34	6	30	320	103	523	20	27	41
21.260.05.11-13	5	13	260	221	353	34	7	30	353	109	525	22	27	67
21.260.08.11-14	8	14	260	218	390	43	7.5	35	330	121	571	28	32	80
21.260.10.11-14	10	14	260	218	429	52	7.5	35	330	137	609	28	32	93
21.300.08.11-13	8	13	300	255	426	43	7	30	370	101	621	22	27	89
21.300.08.11-16	8	16	300	252	420	43	8.5	35	370	111	621	28	32	94
21.300.10.11-16	10	16	300	252	459	52	8.5	35	370	127	659	28	32	91
21.350.10.11-16	10	16	350	305	499	52	8.5	35	435	107	739	28	33	113
21.400.12.11-18	12	18	400	345	557	57	9.5	45	500	125	832	35	37	162
21.450.16.11-20	16	20	450	390	592	57	11	50	550	131	917	35	43	206
21.500.20.11-22	20	22	500	430	592	76	12	50	600	148	1032	40	43	284

Minimum Ultimate Strength = 4 x WLL.

- Standard fitted with becket, cylindrical roller bearing and reeving guide.
- Standard fitted with Crosby type of swivel only hook (319AN style), including safety latch and split pin.
- Standard painted yellow (no striping).
- This crane block may be used with 2 lines only as well.
- Third party testing with certification available upon request.
- Sheaves may be adjustud for other wire rope diameters.
- Becket suitable for connecting Open Wedge Socket for indicated wire rope.
- Becket can not be adjusted.