



Can also be delivered with:



Stock No.	Model No.	WLL (t)	Wire (mm)	Dimensions (mm)									Weight (kg)
				ØD1	ØD2	B	O	TA	TB	TL	T	ØZ	
23.300.016.21	FRB 260.2.16	16	12-14	300	260	650	59	400	165	935	28	32	120
23.365.020.21	FRB 320.2.20	20	15-16	365	320	765	69	450	180	1085	28	32	160
23.410.029.21	FRB 355.2.29	29	17-19	410	355	860	69	500	250	1200	35	37	275
23.460.020.21	FRB 400.2.20	20	24-26	460	400	900	69	570	180	1255	45	52	200
23.460.025.21	FRB 400.2.25	25	24-26	460	400	900	69	570	180	1280	45	52	220
23.460.029.21	FRB 400.2.29	29	20-22	460	400	875	69	570	240	1255	40	43	340
23.515.030.21	FRB 450.2.30	30	24-26	515	450	925	69	605	220	1350	45	52	315
23.515.050.21	FRB 450.2.50	50	24-26	515	450	925	84	605	395	1350	45	52	725
23.595.063.21	FRB 520.2.63	63	27-28	596	528	1160	97	710	405	1640	50	59	1000
23.595.080.21	FRB 520.2.80	80	27-28	596	528	1200	110	710	440	1660	50	59	1050

Minimum Ultimate Strength = 4 x WLL.

- Standard fitted with cylindrical roller bearing, reeving guide and becket.
- Standard painted in yellow with black stripes.
- Standard sheaves of reeve blocks can be adjusted to other wire rope diameters.
- Third party testing with certification available upon request.
- Standard fitted with hook according DIN 15401