

## Sheaves with cylindrical roller bearings

Stock No.	Model No.	Wire (mm)	Dimensions (mm)							Bearing	Material	Weight (kg)
			ØD1	ØD2	E	F	ØG	ØH	R			
31.550.70.03		34	550	480	70	80/54	70	170	18	NNF 5014	GGG-70	55
31.560.50.03	SE.482.5018.11	20	560	482	62	67	90	200	11	NNF 5018	GGG-50	38.7
31.570.50.03	SE.500.5018.13.5	25	570	500	59	67	90	200	13.5	NNF 5018	GGG-50	38.7
31.595.50.03	SE.528.5018.13	24	595	528	61	67	90	200	13	NNF 5018	GGG-50	48.7
31.596.50.03	SE.528.5024.13.5	25	595	528	75	80	120	270	13.5	NNF 5024	GGG-50	55.2
31.600.70.03		36	600	520	85	105/60	80	190	19	NNF 5016	GGG-70	80
31.650.50.03	SE.575.5022.14	27	650	575	75	80	100	280	14	NNF 5022	GGG-50	55.5
31.651.50.03	SE.575.5024.14	27	650	575	72	80	120	280	14	NNF 5024	GGG-50	64
31.665.70.03		38	665	560	100	110	100	210	20.5	NNF 5020	GGG-70	110
31.710.50.5022	SE.630.5022.16	30	710	630	70	80	110	230	16	NNF 5022	GGG-50	66.5
31.710.50.5024	SE.630.5024.17	32	710	630	70	80	120	230	17	NNF 5024	GGG-50	92
31.710.70.03		40	710	630	85	110/80	120	260	21.5	NNF 5024	GGG-70	125
31.800.50.5022	SE.710.5022.18	36	800	710	72	80	110	230	18	NNF 5022	GGG-50	86.5
31.800.50.5024	SE.710.5024.20	38	800	710	72	80	120	230	20	NNF 5024	GGG-50	87
31.800.50.5026	SE.710.5026.18	36	800	710	78	95	130	230	18	NNF 5026	GGG-50	94
31.810.60.03		44	810	710	98	100	150	270	23.5	NNF 5030	GGG-60	190
31.860.50.5026B	SE.710.5026.20	38	860	760	85	95	130	300	20	NNF 5026	GGG-50	100
31.860.50.5030	SE.710.5030.20	38	860	760	85	100	150	300	20	NNF 5030	GGG-50	103
31.890.50.5022	SE.800.5022.16	30	890	800	70	80	110	270	16	NNF 5022	GGG-50	102.5
31.890.50.5024	SE.800.5024.16	30	890	800	70	80	120	270	16	NNF 5024	GGG-50	103
31.890.50.5026	SE.800.5026.20	38	890	800	75	95	130	270	20	NNF 5026	GGG-50	106
31.890.50.5030	SE.800.5030.20	38	890	800	85	100	150	270	20	NNF 5030	GGG-50	128
31.920.60.03		42	920	800	100	109	160	330	22	NNF 5032	GGG-60	215
31.1030.20.03		48	1030	920	130	150	160	400	24.5	NNF 5032	GS20Mn5	380
31.1160.30.03		52	1160	1020	140	160	180	460	22	NNF 5036	GS30Mn5	540

- Different shaft sizes possible.
- Groove may be adjusted to other wire rope diameters.